

LTE09

STANDARD CONFIGURATION

Technical Parameter

power	7KW
Bucket Capacity	0.023m ³
Engine Model	KOOP KD192F
Operation Weight	900kg
Max Digging Force	7.5kN
Hydraulic Pump	Gear Pump
Hydraulic system working pressur	18Mpa
Swing Speed	12rpm
Traveling Speed	2.2km/h
Grade ability	30°
Ground Pressure	19kpa

Operation Parameters

Max. digging distance	2575mm
Max. Digging Depth	1715mm
Max. Digging Height	2560mm
Max. Dumping Height	1780mm
Max. Digging Radius	1480mm
Max. Dozer Cutting	150mm
Max. Dozer Lifting	100mm

Size

Overall Width	720mm
Overall height	2030mm
Seat height	1300mm
Overall Length	2600mm
Mini Ground clearance	80mm
Track ground length	1140mm
Track width	150mm

※The parameters are subject to change without notice



OPTIONAL CONFIGURATION



STANDARD CONFIGURATION

Changchai 192F diesel engine / High-precision multitandem valve / High-quality motor / Nine-tooth spline / gear pump / Imported cylinder, tubing with build-in NOK sealing ring / Adjustable blade / Wear-resistant / engineering rubber track / Adjustable driver seat / Standard bucket / Steyr / Flameout cable

APPLICATION

Applicable to agroforestry planting, farmland leveling, garden cultivation, repairing pavement, basement and interior construction, farming, vegetable greenhouse and other working environment.

