

LTE06

STANDARD CONFIGURATION

OPERATING WEIGH	600kg
BUCKET CAPACITY	0.02 m ³
ENGINE	Koop192/GASOLINE ENGINE: XR2100 (7.6kw/3000/10kw/3600)
MAXIMUM EXCAVATION FORCE	11kn
ROTATION SPEED	12rpm
WALKING SPEED	2km/h
GROUND SPECIFIC VOLTAGE	20kpa
FUEL TANK CAPACITY	5L
HYDRAULIC TANK CAPACITY	12L
MAXIMUM FLOW	6L/cc
RATED WORKING PRESSURE MPA	20mpa
LENGTH * WIDTH * HEIGHT	2750*720*1500mm
MINIMUM GROUND CLEARANCE	180mm
TRACK WIDTH	150mm
GAUGE	420mm
TRACK GROUNDING LENGTH	1100mm
MAXIMUM EXCAVATION HEIGHT	2350mm
MAXIMUM UNLOADING HEIGHT	1600mm
MAXIMUM MINING RANGE	1400mm
MAXIMUM MINING RANGE	4050mm
MINIMUM RADIUS OF GYRATION OF TAIL	500mm
GYRATION RADIUS OF WORKING DEVICE	950mm
CLIMBING ABILITY DEGREE	30°
BOOM SIDE SWING (LEFT/RIGHT)	45/45°

※The parameters are subject to change without notice



OPTIONAL CONFIGURATION



STANDARD CONFIGURATION

Changchai 192F diesel engine / High-precision multi-way valve/ High-quality motor / Nine-tooth spline gear pump / Imported cylinders, tubing with build-in NOK sealing ring / Adjustable blade / Foot pedal/Wear-resis- tant engineering rubber track / Adjustable driver's seat/Standard bucket

APPLICATION

Applicable to agroforestry planting, farmland leveling, garden cultivation, repairing pavement, basement and interior construction, farming, vegetable greenhouse and other working environment.

